

Quality - Put to the Test

Industry Leading Quality Standards

Test	Industry Standard	Porcelain Results	Glass Results	Conclusion
ASTM C1026				
Resistance to Freeze-Thaw Cycling	Subject to a minimum of 300 cycles of freeze-thaw testing	NO visible evidence of freeze-thaw damage	NO visible evidence of freeze-thaw damage	Industry leading performance
ASTM C373				
Average Water Absorption	< 3.0%	< 0.5%	< 0.5%	Vitreous / Impervious Classifications
ASTM C650				
Resistance to Pool Chemicals	Soak in test solution for 24 hrs. at 74°F	No visual effect	No visual effect	Impervious to common pool chemicals
ASTM C648				
Average Breaking Strength	> 250 lbf.	>292 lbf.	Varies	Exceeds Standard
ANSI A137.2-7.9				
Thermal Shock Resistance	Subject to 10 cycles of thermal shock immersion test	No visual effect	No visual effect	Thermal shock resistant

The Artistry In Mosaics Guarantee – The complete range of Artistry In Mosaics products will meet or exceed these standards. Please visit www.artistryinmosaics.com/warranty for full warranty information.

Shade and size variations are inherent characteristics in all porcelain and glass tile products. These variations are a trademark of handcrafted quality and add to the unique beauty of your individual mosaic.

All pool and spa installations must conform to current Tile Council of North America installation guidelines.

All dimensions in this catalog are height x width. Please note that all images are not necessarily proportionate to each other.

All images and designs ©2003-2025 Artistry In Mosaics, Inc.